Link do produktu: https://www.pcomp3000.pl/asus-prime-b660m-a-d4-lga1700-4ddr4-hdmi-dp-p-9143.html



Asus PRIME B660M-A D4 LGA1700 4DDR4 HDMI DP

Cena brutto	**599,00 zł**
Cena netto	**486,99 zł**
Numer katalogowy	**35086916**
Kod producenta	**PRIME B660M-A D4**
Kod EAN	**4711081508014**

Opis produktu

Płyta główna ASUS PRIME H510M-K

GALERIA

SPECYFIKACJA

Procesor: Intel® Socket LGA1700 for 12th Gen Intel® Core™, Pentium® Gold and Celeron® Processors, Intel® Socket LGA1700 for 12th Gen Intel® Core™, Pentium® Gold and Celeron® Processors, Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0

Chipset: Intel® B660 Chipset

Pamięć: 4 x DIMM, Max. 128GB, DDR4, 5333(OC) / 5000(OC) / 4800(OC) / 4600(OC) / 4400(OC) / 4266(OC) / 4000(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3400(OC) / 3333(OC) / 3200 / 3000 / 2933 / 2800 / 2666 / 2400 / 2133 Non-ECC, Un-buffered Memory

Grafika: 1 x DisplayPort, 2 x HDMI® ports

Obsługa Multi-GPU: Brak

Gniazda rozszerzeń

Intel® 12th Gen Processors

- 1 x PCIe 4.0/3.0 x16 slot

Intel® B660 Chipset

- 1 x PCIe 3.0 x16 slot (supports x4 mode)
- 1 x PCIe 3.0 x16 slot (supports x1 mode)

Magazyn danych

2 x M.2 slots and 4x SATA 6Gb/s ports

Intel® 12th Gen Processors

- M.2_1 slot (Key M), type 2242/2260/2280

Intel® 12th Gen processors support PCIe 4.0 x4 mode.

Intel® B660 Chipset

- M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode)*
- 4 x SATA 6Gb/s ports

Sieć LAN

- 1 x Intel® 1Gb Ethernet

Sieć bezprzewodowa: Brak

Bluetooth: Brak

Porty USB

USB z Tyłu (Łącznie 6 portów)

- 2 x USB 3.2 Gen 2 ports (2 x Type-A)
- 4 x USB 2.0 ports (4 x Type-A)

USB z Przodu (Łącznie 10 portów)

- 2 x USB 3.2 Gen 1 headers support additional 4 USB 3.2 Gen 1 ports
- 1 x USB 3.2 Gen 1 connector (supports USB Type-C®)
- 2 x USB 2.0 headers support additional 4 USB 2.0 ports
- 1 x USB 2.0 header support 1 USB 2.0 port

Dźwięk

ALC897

- Realtek 7.1 Surround Sound High Definition Audio CODEC*
- Supports: Jack-detection, Multi-streaming, Front Panel Jack-retasking
- Supports up to 24-Bit/192 kHz playback

Audio Features

- Audio Shielding
- Premium audio capacitors
- Dedicated audio PCB layers

Tylne porty wejścia/wyjścia

- 2 x USB 3.2 Gen 2 ports (2 x Type-A)
- 4 x USB 2.0 ports (4 x Type-A)
- 1 x DisplayPort
- 2 x HDMI® ports
- 1 x Intel® 1Gb Ethernet port
- 3 x Audio jacks

- 1 x PS/2 Keyboard/Mouse combo port

Wewnętrzne porty wejścia/wyjścia

Związane z wiatrakami i chłodzeniem

- 1 x 4-pin CPU Fan header
- 1 x 4-pin CPU OPT Fan header
- 2 x 4-pin Chassis Fan headers

Związane z zasilaniem

- 1 x 24-pin Main Power connector
- 1 x 8-pin +12V Power connector

Związane z magazynowaniem

- 2 x M.2 slots (Key M)
- 4 x SATA 6Gb/s ports

USB

- 2 x USB 3.2 Gen 1 headers support additional 4 USB 3.2 Gen 1 ports
- 1 x USB 3.2 Gen 1 connector (supports USB Type-C®)
- 2 x USB 2.0 headers support additional 4 USB 2.0 ports
- 1 x USB 2.0 header supports 1 USB 2.0 port

Różne

- 3 x AURA Addressable Gen 2 headers
- 1 x AURA RGB header
- 1 x Clear CMOS header
- 1 x COM Port header
- 1 x Front Panel Audio header (AAFP)
- 1 x LPT header
- 1 x S/PDIF Out header
- 1 x SPI TPM header (14-1pin)
- 1 x 20-3 pin System Panel header with Chassis intrude function

Funkcje specjalne

ASUS 5X PROTECTION III

- DIGI+ VRM
- Enhanced DRAM Overcurrent Protection
- ESD Guards
- LANGuard
- Overvoltage Protection
- SafeSlot Core+
- Stainless-Steel Back I/O

ASUS Q-Design

- Q-DIMM
- Q-Slot

ASUS Thermal Solution

- M.2 heatsink
- VRM heatsink design

ASUS EZ DIY

- ProCool

AURA Sync

- AURA RGB header

- Addressable Gen 2 RGB headers

Funkcje oprogramowania

ASUS Exclusive Software

- Armoury Crate
- AURA Creator
- AURA Sync
- Fan Xpert 2+
- AI Suite 3
- - Performance And Power Saving Utility
- TurboV EVO
- EPU
- Digi+ VRM
- ASUS CPU-Z
- Norton Anti-virus software (Free Trial version)
- WinRAR

UEFI BIOS

- ASUS EZ DIY
- ASUS CrashFree BIOS 3
- ASUS EZ Flash 3
- ASUS UEFI BIOS EZ Mode

BIOS

- 128 Mb Flash ROM, UEFI AMI BIOS
- Zarządzanie
- WOL by PME, PXE

Akcesoria

Kable

- 2 x SATA 6Gb/s cables

Różne

- 1 x I/O Shield
- 1 x M.2 Rubber Package
- 1 x M.2 SSD screw package

Media instalacyjne

- 1 x Support DVD

Dokumentacja

- 1 x User manual

Wspierane systemy operacyjne

- Windows® 11 64-bit,
- Windows® 10 64-bit

Typ obudowy

- microATX
- 24.4cm x 24.4cm